

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST AND NORTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 6 AND 7,

IN

TOWNSHIP 2 SOUTH, RANGE 7 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Daniel T. Gillins
Cadastral Surveyor

Under Special Instructions dated **April 21, 2009**, approved **April 21, 2009**, which provided for the surveys included under Group Number **1107**, and Assignment Instructions dated **April 21, 2009**.

Survey Commenced, **April 29, 2009**
Survey Completed, **May 1, 2009**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE WEST AND NORTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 6 AND 7,

IN

TOWNSHIP 2 SOUTH, RANGE 7 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Daniel T. Gillins
Cadastral Surveyor

Under Special Instructions dated **April 21, 2009**, approved **April 21, 2009**, which provided for the surveys included under Group Number **1107**, and Assignment Instructions dated **April 21, 2009**.

Survey Commenced, **April 29, 2009**
Survey Completed, **May 1, 2009**

INDEX DIAGRAM

Township 2 South, Range 7 West.

3 6	8 5	4	3	2	1
7 7 3	6 8	9	10	11	12
5 18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 6.....Page 9
The Subdivision of Section 7.....Page 12

TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the west and north boundaries, and a portion of the subdivisional lines, and the subdivision of sections 6 and 7, in Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by		Retr. Or Resurveyed by	
SOUTH BOUNDARY				
Portion	J. Gorlinski	1877		
Portion	R.C. Yundt & D. Broun	1937		
Portion			R.K. Baugh	2004
EAST BOUNDARY				
All	J.R. Stewart & C.L. Heist	1912		
All			D.T. Gillins & R.K. Baugh	2007
WEST BOUNDARY				
All	J. Gorlinski	1871		
Portion			R.K. Baugh	2004
Portion			D.T. Gillins & R.K. Baugh	2007
NORTH BOUNDARY				
Portion	J. Gorlinski	1871		
All	A.J. Stookey	1906	A.J. Stookey	1906
Portion			R.C. Yundt & D. Broun	1937
SUBDIVISION				
Portion	J. Gorlinski	1877		
Portion	R.C. Yundt & D. Broun	1937	R.C. Yundt & D. Broun	1937
Portion			R.K. Baugh	2004
PRIVATE SURVEYS				
Section 6			N.C. Hathcock, L.S. 166346	2003
Section 7			M.D. Hoffman, L.S. 316831 (Mcneil Engineering)	2007

TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1107, dated April 21, 2009.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods*, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observation of the corner of sections 6 and 7 only, Township 2 South, Range 7 West; post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): KENNECOTT1UT2005 CORS ARP, SALT LAKE CITY CORS ARP, and SALT LAKE WAAS 1 CORS ARP. The geographic position of the said corner is as follows:

Latitude: 40°39'57.008" N.

Longitude: 112°39'59.948" W., N.A.D. 1983,

Network Accuracy = 0.100 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the West Boundary of
Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
J. Gorlinski in 1871, and the Resurvey Executed by
D.T. Gillins and R.K. Baugh in 2007.

Beginning at the corner of sections 7, 12, 13, and 18, on the west boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2007 resurvey.

Corner is located online of a wood fence for a corral extending north and south.

N. 0° 32.4' E., between sections 7 and 12.

- 20.087 Point for the S 1/16 section corner of sections 7 and 12, not monumented.
- 40.174 The 1/4 section corner of sections 7 and 12, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2007 resurvey.

Dependent Resurvey of a Portion of the North Boundary of
Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed
by J. Gorlinski in 1871 and the
Resurvey Executed by A.J. Stookey in 1906.

From the corner of sections 5, 6, 31, and 32, on the north boundary of the township, monumented with an iron post, 2 inches diameter, 36 inches long, loosely set, projecting 28 inches above a small mound of stone, with brass cap marked as described in the official record of the 1937 resurvey.

At the corner point

Reset the iron post 20 inches in the ground, in a mound of stone, 3 ft. base, 16 inches high to top. Add marks "2009" to brass cap.

Corner is located alongside a fence corner with barbed wire

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.
CHAINS

fences extending north, west, and south-southeast.

S. 89° 59.8' W., between sections 6 and 31.

- 19.586 Point selected for the witness E 1/16 section corner of sections 6 and 31.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

WC
S31
E 1/16 ←
S6
2009

Corner is located online of a barbed wire fence extending northeast and southwest, and 1.5 ft. north of a fence extending east.

- 20.030 True point for the E 1/16 section corner of sections 6 and 31, falls on shoulder of State Route 196, bears northeast and southwest, where it is impracticable to establish a permanent monument.
- 40.060 The 1/4 section corner of sections 6 and 31, perpetuated and recorded by Nolan C. Hathcock, Registered Land Surveyor No. 166346, in 2003, remonumented with an iron pipe, 2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap, 3 inches diameter, marked:

TOOELE COUNTY SURVEYOR
T1S
R7W
S31
1/4 —
S6
T2S
2003

Note: Mr. Hathcock determined the corner position at the position of a marked stone as per his 2003 record of survey plat filed at the Tooele County Surveyor's Office, No. 04-0041-01. This stone is currently buried alongside the iron pipe. This point is accepted as a careful and faithful perpetuation of the original corner position.

Corner is located online of a barbed wire fence extending east and west, 45 ft. north of center line of gravel road, bears east and west, and 2 ft. east of barbed wire fence extending north.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 89° 56.6' W., beginning new measurement.

- 40.116 The corner of Townships 1 and 2 South, Ranges 7 and 8 West, monumented with an iron pipe, 2 inches diameter, firmly set, in a mound of stone, 3 ft. base, 6 inches high, to top, with a 2003 Tooele County Surveyor's brass cap, 3 inches diameter, marked as described in the official record of the 2007 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines in
Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by
J. Gorlinski in 1877.

From the corner of sections 7 and 18 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1937 resurvey; with a mound of stone, 3 ft. base, 1 ft. high, 3 links west.

Set a steel fence post alongside iron post.

Corner is located 120 ft. west of center line of dirt road, bears southeast and northwest.

N. 89° 51.6' W., between sections 7 and 18.

- 40.074 Point for the 1/4 section corner of sections 7 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 24 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T2S R7W
S7
1/4 ———
S18
2009

Corner is located 23 ft. south of center line of gravel road, bears northeast and southwest.

Set a steel fence post alongside aluminum post.

- 60.100 Point selected for the witness W 1/16 section corner of sections 7 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

WC
S7
W 1/16 ←
S18
2009

- 60.111 True point for the W 1/16 section corner of sections 7 and 18, falls on top of a steel fence corner post, 2 1/2 inches diameter, projecting 4.4 ft. above a concrete pillar, 16 inches diameter, with barbed wire fences extending north and west.

Note: This point was monumented by Michael D. Hoffman, Registered Land Surveyor No. 316831, with a rebar as per his 2007 record of survey plat filed in the Tooele County Surveyor's Office, No. 07-0140-01. The rebar, 5/8 inch diameter, with red plastic cap marked "Mcneil Engr" is lying alongside the fence corner post. It was likely disturbed during construction of the fence.

- 79.747 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

Reestablishment of the Survey Executed by
J. Gorlinski in 1877, and the Resurvey Executed by
R.C. Yundt and D. Broun in 1937.

From the corner of sections 7 and 18 only.

N. 0° 25.0' E., along the east boundary of section 7.

- 32.517 The 1/4 section corner of section 8 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above a mound of stone, 4 ft. base, 8 inches high, with brass cap marked as described in the official record of the 1937 survey.

Set a steel fence post 2.5 ft. south of iron post.

- 40.280 The 1/4 section corner of section 7 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1937 resurvey; with a mound of stone, 3 ft. base, 1 1/2 ft. high, 3 links west.

Set a steel fence post alongside iron post.

N. 0° 19.2' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

32.121 The closing corner of sections 5 and 8, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above a mound of stone, 4 ft. base, 6 inches high, with brass cap marked as described in the official record of the 1937 survey.

40.371 The corner of sections 6 and 7 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 9 inches above the ground, in a scattered mound of stone, with brass cap marked as described in the official record of the 1937 resurvey.

Corner is located 12 ft. north of center line of dirt road, bears east and west, and 140 ft. north of a barbed wire fence extending east and west.

Set a steel fence post alongside iron post.

Reestablishment of the Survey Executed by
J. Gorlinski in 1877.

S. 89° 52.4' W., between sections 6 and 7.

20.096 Point for the E 1/16 section corner of sections 6 and 7.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

S6
E 1/16 ———
S7
2009

Corner is located 37 ft. north of center line of dirt road, bears east and west, and 75 ft. north of barbed wire fence extending east and west.

Set a steel fence post 1.75 ft. north of iron post.

40.192 Point for the 1/4 section corner of sections 6 and 7, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T2S R7W
S6
1/4 ———
S7
2009

Corner is located 10 ft. west of westerly edge of pavement of State Route 196, bears northeast and southwest.

- 79.781 The corner of sections 1, 6, 7, and 12, on the west boundary of the township, monumented with an iron pipe, 2 inches diameter, firmly set, projecting 7 inches above the ground, with a 2003 Tooele County Surveyor's brass cap, 3 inches diameter, marked as described in the official record of the 2007 resurvey.

Reestablishment of the Survey Executed by
J. Gorlinski in 1877, and the Resurvey Executed by
R.C. Yundt and D. Broun in 1937.

From the corner of sections 6 and 7 only.

N. 0° 33.9' E., along the east boundary of section 6.

- 20.176 Point for the S 1/16 section corner of section 6 only, not monumented.

- 31.746 The 1/4 section corner of section 5 only, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, 4 ft. base, 16 inches high, to top of brass cap marked as described in the official record of the 1937 resurvey; with a mound of stone, 3 ft. base, 2 ft. high, 3 links east.

Set a steel fence post 2 ft. west of iron post.

- 40.352 The 1/4 section corner of section 6 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1937 resurvey; with a mound of stone, 4 ft. base, 2 ft. high, 4 links west.

Set a steel fence post alongside iron post.

N. 0° 39.6' E., beginning new measurement.

- 19.969 Point for the N 1/16 section corner of section 6 only.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N 1/16 |
S6 |
2009

Set a steel fence post alongside aluminum post.

Raise mound of stone, 3 ft. base, 1 1/2 ft. high, 3 links west of corner.

Corner is located 35 ft. west of barbed wire fence extending north and south.

- 31.363 The 80th chain 1/16 section corner of section 5 only, determined along west edge of an embedded mound of stone, 3 ft. base, 6 inches high. Did not find the record 1937 iron post. This embedded mound is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

| 1/16 80
S5
2009

Corner is located 45 ft. west of barbed wire fence extending south-southeast and north-northwest.

- 39.539 The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

The Subdivision of Section 6 in
Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 6 and 7.

N. 0° 42.0' E., along the N-S center line of section 6.

- 20.090 The center S 1/16 section corner of section 6, monumented by Nolan C. Hathcock, Registered Land Surveyor No. 166346, with a rebar, 5/8 inch diameter, with yellow plastic cap marked "HATHCOCK LS 166346", as described in his 2003 record of survey plat filed in the Tooele County Surveyor's Office, No. 04-0041-01. The rebar is accepted as a careful and faithful determination of the corner position. The rebar is firmly set, projecting 4 inches above the ground, with a steel fence

THE SUBDIVISION OF SECTION 6 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

post alongside.

At the corner point

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, with aluminum cap marked:

C
S 1/16 | S6
C
2009

Deposit rebar inside aluminum post.

- 40.180** The center 1/4 section corner of section 6, monumented by Nolan C. Hathcock, Registered Land Surveyor No. 166346, with a rebar, 5/8 inch diameter, with yellow plastic cap marked "HATHCOCK LS 166346", as described in his 2003 record of survey plat filed in the Tooele County Surveyor's Office, No. 04-0041-01. The rebar is accepted as a careful and faithful determination of the corner position. The rebar is firmly set, projecting 4 inches above the ground.

At the corner point

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 29 inches in the ground, with aluminum cap map:

T2S R7W
C 1/4 S6
2009

Deposit rebar inside aluminum post.

- 60.179** The center N 1/16 section corner of section 6, monumented by Nolan C. Hathcock, Registered Land Surveyor No. 166346, with a rebar, 5/8 inch diameter, with yellow plastic cap marked "HATHCOCK LS 166346", as described in his 2003 record of survey plat filed in the Tooele County Surveyor's Office, No. 04-0041-01. The rebar is accepted as a careful and faithful determination of the corner position. The rebar is firmly set, projecting 4 inches above the ground.

- 79.978** The 1/4 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of section 6 only.

S. 89° 37.4' W., along the E-W center line of section 6.

- 20.048** Point for the center E 1/16 section corner of section 6, not monumented.

THE SUBDIVISION OF SECTION 6 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.096 The center 1/4 section corner of section 6.
- 79.945 The 1/4 section corner of sections 1 and 6, monumented with an iron pipe, 2 inches diameter, firmly set, projecting 8 inches above the ground, with a 2003 Tooele County Surveyor's brass cap, 3 inches diameter, marked as described in the official record of the 2007 resurvey.
-
- From the point for the center E 1/16 section corner of section 6.
- N. 0° 40.8' E., along the N-S center line of the NE 1/4 of section 6.
- 19.985 Point for the NE 1/16 section corner of section 6, at the intersection with the E-W center line of the NE 1/4.
- Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, with aluminum cap marked:
- NE 1/16 S6
2009
- Set a steel fence post alongside aluminum post.
- Corner is located 143 ft. north of barbed wire fence extending east and west.
- 39.669 The true point for the E 1/16 section corner of sections 6 and 31, on the north boundary of the township.
-
- From the N 1/16 section corner of section 6 only.
- S. 89° 40.2' W., along the E-W center line of the NE 1/4 of section 6.
- 20.039 The NE 1/16 section corner of section 6.
- 40.078 The center N 1/16 section corner of section 6.
-
- From the E 1/16 section corner of sections 6 and 7.
- N. 0° 37.9' E., along the N-S center line of the SE 1/4 of section 6.
- 20.133 Point for the SE 1/16 section corner of section 6, at the intersection with the E-W center line of the SE 1/4.
- Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 27 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 6 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

SE 1/16 S6
2009

Set a steel fence post alongside aluminum post.

- 40.266 The point for the center E 1/16 section corner of section 6.
-

From the point for the S 1/16 section corner of section 6 only.

S. 89° 45.0' W., along the E-W center line of the SE 1/4 of section 6.

- 20.072 The SE 1/16 section corner of section 6.

- 40.144 The center S 1/16 section corner of section 6.
-

The Subdivision of Section 7 in
Township 2 South, Range 7 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 7 and 18.

N. 0° 16.7' E., along the N-S center line of section 7.

- 20.107 Point selected for the witness center S 1/16 section corner of section 7.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

WC
↑
C
S 1/16 | S7
C
2009

- 20.114 True point for the center S 1/16 section corner of section 7, falls along south side of a steel fence corner post, 2 1/2 inches diameter, projecting 4.4 ft. above a concrete pillar, 16 inches diameter, with barbed wire fences extending north and west.

Note: This point was monumented by Michael D. Hoffman, Registered Land Surveyor No. 316831, with a rebar as per his 2007 record of survey plat filed in the Tooele County Surveyor's Office, No. 07-0140-01. The rebar, 5/8 inch diameter, with red plastic cap marked "Mcneil Engr" is lying alongside the fence corner post. It was likely disturbed during construction of the fence.

THE SUBDIVISION OF SECTION 7 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.228 Point for the center 1/4 section corner of section 7, at the intersection with the E-W center line of section.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 26 inches in the ground, with aluminum cap marked:

T2S R7W
C 1/4 S7
2009

Corner is located online of a barbed wire fence extending north and south.

- 80.463 The 1/4 section corner of sections 6 and 7.
-

From the 1/4 section corner of section 7 only.

N. 89° 56.1' W., along the E-W center line of section 7.

- 40.167 The center 1/4 section corner of section 7.

- 60.160 Point for the center W 1/16 section corner of section 7, not monumented.

- 79.653 The 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.
-

From the true point for the W 1/16 section corner of sections 7 and 18.

N. 0° 20.3' E., along the N-S center line of the SW 1/4 of section 7.

- 20.100 Point for the SW 1/16 section corner of section 7, at the intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 2 1/2 inches diameter, 30 inches long, 28 inches in the ground, with aluminum cap marked:

SW 1/16 S7
2009

Corner is located online of a barbed wire fence, extending east and west, 2 ft. east of a fence corner for barbed wire fences extending east and south.

Note: Did not find a rebar set at this corner by Michael D. Hoffman, Registered Land Surveyor No. 316831, as per his 2007 record of survey plat filed in the Tooele County Surveyor's

THE SUBDIVISION OF SECTION 7 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Office, No. 07-0140-01. It was likely disturbed during construction of the fence.

40.200 The point for the center W 1/16 section corner of section 7.

From the true point for the center S 1/16 section corner of section 7.

N. 89° 54.0' W., along the E-W center line of the SW 1/4 of section 7.

20.015 The SW 1/16 section corner of section 7.

39.580 The point for the S 1/16 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Chris May	Survey Technician
Matt Gillins	Survey Technician

CERTIFICATE OF SURVEY

I, Daniel T. Gillins, *Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *21st day of April, 2009*, I have *dependently resurveyed a portion of the west and north boundaries, and a portion of the subdivisional lines, and subdivided sections 6 and 7, in Township 2 South, Range 7 West, of the Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 14, 2010

Date

Daniel T. Gillins

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west and north boundaries, and a portion of the subdivisional lines, and the subdivision of sections 6 and 7, in Township 2 South, Range 7 West, Salt Lake Meridian, Utah*, executed by *Daniel T. Gillins, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

October 20, 2010

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)